(19) World Intellectual Property Organization

International Bureau



(43) International Publication Date 10 February 2005 (10.02.2005)

PCT

(10) International Publication Number WO 2005/013400 A2

- (51) International Patent Classification7: H01M 8/02, 8/10
- (21) International Application Number:


PCT/JP2004/011021

- 27 July 2004 (27.07.2004) (22) International Filing Date:
- (25) Filing Language: English
- (26) Publication Language: **English**
- (30) Priority Data:

2003-283974 31 July 2003 (31.07.2003) 2003-283975 31 July 2003 (31.07.2003) JP

- (71) Applicant (for all designated States except US): NISSAN MOTOR CO., LTD. [JP/JP]; 2, Takara-cho, Kanagawa-ku, Yokohama-shi, Kanagawa, 2210023 (JP).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): NAGAYAMA, Mori [JP/JP]. SAITO, Takamitsu [JP/JP]. SHIMAMURA, Osamu [JP/JP].

- (74) Agents: MIYOSHI, Hidekazu et al.; Toranomon Daiichi Building, 9th Floor, 2-3, Toranomon 1-chome, Minato-ku, Tokyo, 1050001 (JP).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AB, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).



material layer (32) formed on a collector (1) has a density gradient developed with (a) gradient(s) of (a) varied concentration(s) of one or both of an electrolyte salt and a film forming material along a thickness from a surface of the electrode active material layer (32) toward the collector (1).

